

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com


Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

FirestoP®

tasker® TSK 1078 L.S.Z.H. – 1x0,52 mm²

Halogen Free

HD SDI - Coaxial Cable 75 Ω - 120 Meters Installation 



CATEGORY Coaxial cable 75 Ω (See Video Catalogue)

APPLICATIONS Digital video for broadcast and high definition video installation

- A:** Dark Blue Soft **L.S.Z.H.** sheath. Flame Retardant e Halogen Free. Outdoor Limited. Outer Diam. Ø 6,00 (±0,20) mm.
- B:** First Shielding O.F.C. tinned copper Braid covering 95%.
- C:** Second Shielding in aluminum foil tape, covering 100 %.
- D:** Core Insulation with Foam PE. Diam. Ø 3,50 (±0,20) mm.
- E:** Stiff Wire formation 1x0,80 mm in O.F.C. Red Copper. Nom. Cross section 1x0,50 mm².

MARKING **tasker®** TSK1078 LSZH – 75Ω – 20 AWG - O.F.C. - GAS INJECTED FHDPE - BROADCAST COAX VIDEO HD- SDI CABLE - FirestoP® - Halogen Free – Made In Italy

CUSTOM PRODUCTION This product may be custom produced also in **PVC, PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	38 Ω/Km
Capacity Core/Shield	53,5 pF/m.
Velocity of Propagation	83%
Impedance	75 Ω
Nom. Delay	4,0 ns/m.
Operative Temperature	-30/+70°C

Attenuation dB/100 m.

10 MHz	2,03
100 MHz	7,31
1000 MHz	24,60
2000 MHz	36,74
3000 MHz	50,11
4500 MHz	67,64

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			